

# TITANIUM D1

## SAE 5W-30

### Full Synthetic Engine Oil

#### Description

Omnecraft Titanium D1 5W-30 is a full synthetic high-performance engine oil, which provides excellent high-temperature protection, even under severe operating conditions.

The oil is designed to help provide long engine life and provide outstanding protection in vehicles of all ages, outperforming our semi-synthetic blended products. It provides outstanding protection against sludge, engine rust, and corrosion under severe and low-temperature operating conditions, and provide optimum viscosity and fluid stability across a broad range of temperatures.

Omnecraft Titanium D1 5W-30 meets or exceeds ILSAC GF-5. The claim is backward compatible with earlier performance levels such as API SM, API SL, API SJ, and previous ILSAC categories.

#### Features and Benefits

- Helps extend engine life
- Outstanding wear protection for vehicles of all ages
- Excellent high-temperature protection to help keep engines cool
- Permits extended operation at elevated temperatures (up to 190°C) without oxidative oil thickening and oil breakdown
- Helps control oil consumption and loss
- Allows easy starting and rapid oil circulation during cold starts to protect critical engine parts
- Protection beyond our semi-synthetic blended products
- API SN Resource Conserving

#### Applications

Omnecraft Titanium D1 5W-30 is recommended for petrol cars and light-duty trucks requiring an API SN, API SM, API SL or API SJ. It meets ILSAC GF-5 (Starburst Certification Symbol).

#### Specifications and Approvals

Omnecraft Titanium D1 5W-30 meets or exceeds the requirements of: API SN, ILSAC GF-5.



Available in 5L, 20L and 208L  
sizes from Ford Trade Club